


Puddle Flange PE



- for permanent and watertight sealing of PE 100 pipes
- pull out resistant
- prevents penetration of ground- and pressurised water
- with sufficient long spigots for electro fusion or butt welding
- EPDM collar fixed with stainless steel bands and fasteners optional without EPDM collar
- can not be considered a fix point
- Standards / guidelines: DIN EN 12201, DVS 2207 & 2210, DIN EN 10204, DIN EN ISO 9001, DIN EN ISO 50001



d1	la1	b	D	Z	PN 10 / KG	PN 16 / KG
90	500	70	210	1140	2,2	3,2
110	500	70	225	1140	3,1	4,4
125	500	70	240	1140	4,2	6,0
140	500	70	260	1140	4,8	7,0
160	500	70	280	1140	6,2	9,0
180	500	70	300	1140	7,6	11,2
200	500	70	325	1140	9,7	14,1
225	500	70	350	1140	12,0	17,5
250	500	70	380	1140	14,7	21,7
280	500	70	415	1140	18,1	26,9
315	500	90	430	1200	23,9	35,6
355	500	90	475	1200	30,6	44,9
400	500	90	525	1200	38,3	57,0
450	500	90	575	1200	48,2	71,3
500	500	90	635	1200	59,4	88,2
560	500	90	705	1200	74,2	110,9
630	500	90	785	1200	93,9	140,1
710	500	90	875	1200	118,5	
800	500	90	975	1200	150,8	
900	500	90	1075	1200	188,7	
1000	500	90	1175	1200	224,0	
1200	500	90	1375	1200	306,7	