

Wall Penetration Sealing Sleeve





- for sealing wall penetrations secure and permanently especially of warm going pre-insulated pipes of large dimensions
- fabricated from synthetic elastomer with a thickness of approx. 5 mm
- available in any size of the casing and/or carrier pipe as manufactured to order (provide exact dimensions of the pipes outer diameter and the expected expansion)
- water tight, leak proof against pressing water up to 1 bar at max. 75 mm annular space, when annular space > 75 mm please consult us (MFPA approved with load cycles between wall and carrier pipe)
- temperature resistant max. +55°C, for higher temperatures please consult us (provide exact dimensions of the pipes outer diameter and the expected expansion)
- delivered together with a set consisting of 2 x 2 19 mm wide stainless steel bands with fasteners and special one-component adhesive in a can of 310 ml
- for pipes > DN 300 we deliver hinge bolt tightening stainless steel bands with TOX Weld Point Freecorrosion jointing technology, no welding for optimised corrosion protection

Mounting advice

- apply adhesive inside of both sleeve ends and fasten it with the 2 x 2 stainless steel bands and fasteners
- the stainless steel bands press the sleeve firmly onto the pipe and hold the sleeve and the sealing adhesive in position
- in case a tightening tool for fixing the stainless steel bands is required this would have to be ordered separately
- to prevent eventually expansion of the pipe, it is advisable to create in front of the sleeve an expansion zone by a compensation cushion (e.g. sand bed)



S-shape expansion direction



stretched expansion direction

The **KONEX** INTERNATIONAL guarantee for Wall Penetration Sealing Sleeve Type MRKK is limited to failures in the material. The user is responsible for their individual application.







before backfilling protect sealing sleeves with expansion pad



Wall Penetration Sealing Sleeve

Type MRKK

OD	х	DN mm	OD	х	DN mm	
75	х	100	315	Х	400	
75	х	125	315	Х	450	
75	х	150	355	х	450	
75	х	200	355	х	500	
90	х	150	400	х	450	
90	х	200	400	Х	500	
90	х	250	400	Х	550	
110	х	150	450	х	500	
110	х	200	450	Х	550	
110	х	250	450	х	600	
125	х	150	500	х	600	
125	х	200	500	Х	650	
125	х	250	560	Х	650	
140	х	200	560	Х	700	
140	х	250	630	Х	700	
140	х	300	630	Х	750	
160	х	200	670	Х	750	
160	х	250	670	Х	800	
160	х	300	710	Х	800	
200	х	250	710	Х	850	
200	х	300	800	Х	900	
200	х	350	800	Х	950	
225	х	300	900	Х	1000	
225	Х	400	900	Х	1050	
250	Х	300	1000	Х	1100	
250	Х	350	1000	Х	1150	
250	Х	400	1100	Х	1200	
315	Х	350	1200	Х	1300	
315	Х	400				



KONEX INTERNATIONAL • D-79771 Klettgau-Erzingen • Saizig 5 • Germany Tel. +49 (0) 7742 4399 • Fax. +49 (0) 7742 1083 • export@konex-international.com • www.konex-international.com